

View Online at <https://aerobasegroup.com/nsn/5306-00-282-6272>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.288 inches and 1.338 inches

Fastener Length:

Between 3.985 inches and 4.015 inches

Head Diameter:

Between 1.609 inches and 1.625 inches

Head Height:

0.952 inches

Hole Diameter:

0.070 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.146 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

1.000 inches

Width Across Flats:

Between 1.001 inches and 1.005 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.803 inches first hole and 3.823 inches first hole

Material:

Steel comp e4340 or steel comp 8740 or steel comp 6150 or steel comp 3140 or steel comp 3135

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Uns

Specification Data:

80205-nas156 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0