

View Online at <https://aerobasegroup.com/nsn/5306-00-282-8976>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.406 inches

Eye Inside Diameter:

Between 0.188 inches and 0.191 inches

Shoulder Thickness:

0.062 inches

Shank Length:

4.406 inches

Eye Stock Thickness:

0.094 inches

Shoulder Diameter:

0.438 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole

Overall Length:

5.062 inches

Thread Diameter:

0.190 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Distance From Threaded End To Shank Hole Center:

4.266 inches first hole

Eye Outside Width:

0.438 inches

Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140

Material Specification:

Mil-b-6812 military specification all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Style Designator:

Round, closed w/shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-b-6812 spec.