

View Online at <https://aerobasegroup.com/nsn/5306-00-282-9315>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.788 inches and 0.838 inches

**Fastener Length:**

Between 1.735 inches and 1.765 inches

**Head Style:**

Bevel-conical

**Head Diameter:**

Between 0.740 inches and 0.750 inches

**Head Height:**

0.407 inches

**Hole Diameter:**

0.070 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.437 inches

**Width Across Flats:**

Between 0.375 inches and 0.378 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hole Configuration Style:**

Round internal hexagon

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.444 inches first hole and 1.464 inches first hole

**Material:**

Steel comp e4340 or steel comp 8740 or steel comp 6150 or steel comp 3140 or steel comp 3135

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas147 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0