

View Online at <https://aerobasegroup.com/nsn/5306-00-282-9316>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.812 inches

**Fastener Length:**

Between 1.7975 inches and 1.8275 inches

**Head Style:**

Bevel-conical

**Head Diameter:**

Between 0.740 inches and 0.750 inches

**Head Height:**

0.407 inches

**Hole Diameter:**

0.055 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.438 inches

**Width Across Flats:**

Between 0.3755 inches and 0.3785 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hole Configuration Style:**

Round

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.516 inches first hole

**Material:**

Steel comp 4140 or steel comp 6150 or steel comp 8740 or steel comp 3140

**Material Specification:**

Mil-s-5000 cond c, 4 military specification 1st material response or mil-s-6059 cond c, 4 military specification 2nd material response or mil-s-8503 cond c, 4 military specification 3rd material response or qq-s-690 cond e, 4 federal specification 4th material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.