
NSN 5306-00-283-0383

Machine Bolt - Page 1 of 2





Thread Class: 2a **Thread Direction: Right-hand Thread Length:** 0.500 inches Fastener Length: Between 0.719 inches and 0.750 inches **Head Style:** Hexagon **Head Height:** Between 0.195 inches and 0.211 inches Width Between Flats: Between 0.484 inches and 0.500 inches Hole Diameter: 0.070 inches **Thread Diameter:** 0.312 inches Grip Length: 0.219 inches **Hole Quantity:** 1 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel **Material Specification:** Sae gr 5 assn standard single material response Surface Treatment: Zinc and phosphate **Surface Treatment Specification:**

Qq-z-325, type 3, class 2 federal specification single treatment response

NSN 5306-00-283-0383

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unf

Specification Or Standard:

Y1 part and 5 grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-1222 spec.

