

View Online at <https://aerobasegroup.com/nsn/5306-00-283-7050>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.403 inches and 0.413 inches

**Fastener Length:**

1.350 inches

**Head Style:**

Round w/wrench flats

**Head Diameter:**

0.875 inches

**Head Height:**

0.120 inches

**Width Between Flats:**

0.750 inches

**Shoulder Diameter:**

0.498 inches first shoulder and 0.499 inches first shoulder

**Shoulder Length:**

0.937 inches first shoulder and 0.947 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.075 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.160 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel

**Material Specification:**

Mil-s-6758, cond 4, surface 4 military specification single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.