

View Online at <https://aerobasegroup.com/nsn/5306-00-285-3239>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.938 inches

Fastener Length:

Between 5.860 inches and 5.890 inches

Head Diameter:

Between 0.988 inches and 1.000 inches

Head Height:

0.595 inches

Hole Diameter:

0.070 inches

Shank Unthreaded Hole Diameter:

5.688 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

0.625 inches

Width Across Flats:

Between 0.563 inches and 0.566 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.141 inches first hole

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas150 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0