NSN 5306-00-285-8426

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-285-8426 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.970 inches and 1.000 inches **Fastener Length: 7.997** inches **Head Style:** Hexagon extended washer **Head Height:** 0.953 inches Width Between Flats: Between 1.296 inches and 1.315 inches **Extended Washer Diameter:** 2.250 inches **Extended Washer Thickness:** 0.180 inches **Shoulder Diameter:** 1.4990 inches and 1.4998 inches first shoulder **Shoulder Length:** 6.787 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.169 inches and 0.175 inches first hole **Thread Diameter:** 0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 270000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 7.781 inches and 7.791 inches first hole **Shoulder Shape:** Round first shoulder **Product Name:** Navy special project Material: Steel

Material Specification: C-05-1190, fscm 36659 mfr ref single material response

Surface Treatment:

Chromium

NSN 5306-00-285-8426

Shoulder Bolt - Page 2 of 2



Lc+77-2035, fscm 36659 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0