

View Online at <https://aerobasegroup.com/nsn/5306-00-286-1971>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.787 inches and 0.837 inches

**Fastener Length:**

Between 1.610 inches and 1.640 inches

**Head Style:**

Bevel-conical

**Head Diameter:**

Between 0.740 inches and 0.750 inches

**Head Height:**

0.438 inches

**Hole Diameter:**

0.055 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.438 inches

**Width Across Flats:**

Between 0.313 inches and 0.315 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

34.0 rockwell c and 40.0 rockwell c

**Hole Configuration Style:**

Round internal hexagon

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.