## NSN 5306-00-288-1957

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-288-1957 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.365 inches and 0.375 inches **Fastener Length:** Between 0.793 inches and 0.823 inches **Head Style:** Dished hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification all treatment responses **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6304 professional/industrial association standard Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5306-00-288-1957

Shear Bolt - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A003b0