

View Online at <https://aerobasegroup.com/nsn/5306-00-288-2475>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.824 inches and 0.874 inches

Fastener Length:

Between 2.709 inches and 2.739 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.547 inches and 0.567 inches

Width Between Flats:

Between 0.616 inches and 0.627 inches

Extended Washer Diameter:

Between 0.928 inches and 0.938 inches

Extended Washer Thickness:

Between 0.123 inches and 0.143 inches

Grip Diameter:

Between 0.5610 inches and 0.5615 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.146 inches first hole

Thread Diameter:

0.562 inches

Grip Length:

Between 1.865 inches and 1.885 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.456 inches first hole and 2.496 inches first hole

Material:

Stainless steel

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0