

View Online at <https://aerobasegroup.com/nsn/5306-00-292-2386>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.503 inches and 0.585 inches

Fastener Length:

Between 3.046 inches and 3.093 inches

Head Style:

Hexagon

Head Height:

0.250 inches

Width Between Flats:

Between 0.865 inches and 0.877 inches

Shoulder Diameter:

0.624 inches first shoulder

Shoulder Length:

2.430 inches first shoulder and 2.470 inches first shoulder

Shank Unthreaded Hole Diameter:

0.107 inches first hole

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.890 inches first hole and 2.922 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.