

View Online at <https://aerobasegroup.com/nsn/5306-00-292-2386>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.503 inches and 0.585 inches

**Fastener Length:**

Between 3.046 inches and 3.093 inches

**Head Style:**

Hexagon

**Head Height:**

0.250 inches

**Width Between Flats:**

Between 0.865 inches and 0.877 inches

**Shoulder Diameter:**

0.624 inches first shoulder

**Shoulder Length:**

2.430 inches first shoulder and 2.470 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.107 inches first hole

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.890 inches first hole and 2.922 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.