## NSN 5306-00-292-2389

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-292-2389 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.446 inches and 0.514 inches **Fastener Length:** Between 2.283 inches and 2.331 inches **Head Style:** Hexagon **Head Height:** 0.156 inches Width Between Flats: 0.750 inches **Shoulder Diameter:** 0.494 inches first shoulder and 0.496 inches first shoulder **Shoulder Length:** 1.708 inches first shoulder and 1.718 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.106 inches first hole **Thread Diameter:** 0.375 inches **Features Provided:** Casehardened Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 2.103 inches first hole and 2.135 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel comp 8620 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5306-00-292-2389

Shoulder Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0