

View Online at <https://aerobasegroup.com/nsn/5306-00-292-4614>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.813 inches and 0.844 inches

Fastener Length:

0.875 inches

Head Style:

Crowned hexagon

Head Height:

0.109 inches

Width Between Flats:

0.375 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 0.031 inches and 0.062 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Special Features:

As modified by slotted shank

Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140

Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response or mil-s-5626 military specification 6th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.