

View Online at <https://aerobasegroup.com/nsn/5306-00-292-5908>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.000 inches

Fastener Length:

1.000 inches

Head Style:

Hexagon

Head Height:

0.234 inches

Width Between Flats:

0.500 inches

Thread Diameter:

0.312 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

75000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1524 or steel comp 1527 or steel comp 1536 or steel comp 1541 or steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl2 federal specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

1 type and 2 grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A003b0

Mil-std (military Standard):

Mil-s-1222 spec.