
NSN 5306-00-292-8160

Internal Wrenching Bolt - Page 1 of 2





| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| |
| Right-hand Thread Length: |
| Between 0.662 inches and 0.712 inches |
| Fastener Length: |
| Between 2.110 inches and 2.140 inches |
| |
| Head Style: Bevel-conical |
| Head Diameter: |
| Between 0.639 inches and 0.649 inches |
| Head Height: |
| 0.375 inches |
| Hole Diameter: |
| |
| 0.055 inches |
| Internal Drive Style: |
| Hexagon Thread Diameter: |
| 0.375 inches |
| Width Across Flats: |
| Between 0.313 inches and 0.315 inches |
| |
| Hole Quantity: |
| |
| Hole Type: Drilled |
| |
| Thready Qty Per Inch (tpi): 24 |
| |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch Hardness Rating: |
| 34.0 rockwell c and 40.0 rockwell c |
| |
| Hole Configuration Style: |
| Round longitudinal hole Material: |
| |
| Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 Surface Treatment: |
| |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2 cl 2 federal specification single treatment response |
| Thread Series Designator: |

Unf

NSN 5306-00-292-8160

Internal Wrenching Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

