

View Online at <https://aerobasegroup.com/nsn/5306-00-297-2568>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.600 inches

**Fastener Length:**

5.300 inches

**Head Style:**

Hexagon

**Head Height:**

0.350 inches

**Width Between Flats:**

1.875 inches

**Shoulder Diameter:**

1.3115 inches first shoulder

**Shoulder Length:**

4.580 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole

**Thread Diameter:**

1.250 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

5.140 inches first hole

**Shoulder Shape:**

Round first shoulder

**Product Name:**

Bolt, inbrd trpd Ink

**Material:**

Steel

**Material Specification:**

Mil-s-5000 cond c2 military specification single material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.