

View Online at <https://aerobasegroup.com/nsn/5306-00-297-2961>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.397 inches and 0.417 inches

Fastener Length:

Between 3.408 inches and 3.413 inches

Head Style:

Hexagon

Head Height:

Between 0.302 inches and 0.322 inches

Width Between Flats:

Between 0.928 inches and 0.948 inches

Shoulder Diameter:

0.623 inches first shoulder and 0.624 inches first shoulder

Shoulder Length:

2.924 inches first shoulder and 2.929 inches first shoulder

Shank Unthreaded Hole Diameter:

0.107 inches first hole

Thread Diameter:

0.500 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.236 inches first hole and 3.241 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp e4340

Material Specification:

Mil-s-5000 military specification single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.