## NSN 5306-00-297-8522

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-297-8522

Thread	Class
Inteau	<b>UIA33</b> .

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

0.297 inches

#### Fastener Length:

1.347 inches

#### **Head Style:**

Hexagon

Head Height:

#### 0.156 inches

#### Width Between Flats:

0.500 inches

#### Shoulder Diameter:

0.3114 inches first shoulder and 0.3119 inches first shoulder

#### Shoulder Length:

0.972 inches first shoulder

#### Shank Unthreaded Hole Diameter:

0.076 inches first hole

#### **Thread Diameter:**

0.250 inches

#### Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

125000 pounds per square inch

## Distance From Head Largest Bearing Surface To Shank Hole Center:

1.137 inches first hole

## Shoulder Shape:

Round first shoulder

## Material:

Steel comp 4130

## Material Specification:

Sae assn standard single material response

## Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

## Thread Series Designator:

Unf

## Shelf Life:

N/a

# NSN 5306-00-297-8522

Shoulder Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

