

View Online at <https://aerobasegroup.com/nsn/5306-00-298-1097>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.920 inches and 1.020 inches

Fastener Length:

2.750 inches

Head Style:

Hexagon extended washer

Head Height:

0.310 inches

Width Between Flats:

Between 0.616 inches and 0.625 inches

Extended Washer Diameter:

0.750 inches

Extended Washer Thickness:

0.060 inches

Shank Unthreaded Hole Diameter:

0.094 inches all holes and 0.101 inches all holes

Thread Diameter:

0.438 inches

Grip Length:

Between 1.730 inches and 1.830 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

20

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.610 inches all holes

Material:

Steel comp 8740 or steel comp 4140

Material Specification:

Ams 6322 assn standard 1st material response or ams 6382 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0