NSN 5306-00-298-1283

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-298-1283

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.610 inches |
| Fastener Length: |
| Between 0.925 inches and 0.945 inches |
| Head Style: |
| Dee |
| Head Diameter: |
| Between 0.490 inches and 0.510 inches |
| Head Height: |
| Between 0.200 inches and 0.220 inches |
| Distance From Centerline To Flat: |
| Between 0.118 inches and 0.123 inches |
| Hole Diameter: |
| 0.062 inches |
| Shank Unthreaded Hole Diameter: |
| 0.075 inches first hole |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| 0.335 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 130000 pounds per square inch |
| Hardness Rating: |
| 28.0 rockwell c |
| Hole Configuration Style: |
| Round |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 0.705 inches first hole |
| Material: |
| Iron alloy 660 |
| |

NSN 5306-00-298-1283

Machine Bolt - Page 2 of 2



| M | late | rial | Sp | ecif | icat | ion: |
|---|------|------|----|------|------|------|
| | | | ~ | •••• | | . • |

Ams 5732 assn standard single material response

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0