## NSN 5306-00-298-3008

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-298-3008 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.353 inches and 0.380 inches **Fastener Length:** Between 0.425 inches and 0.435 inches **Head Style:** Hexagon **Head Height:** Between 0.175 inches and 0.195 inches Width Between Flats: Between 0.493 inches and 0.502 inches **Hole Diameter:** 0.062 inches First Diameter From Head: Between 0.245 inches and 0.255 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.052 inches and 0.072 inches **Thread Diameter:** 0.312 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Hexagon flats **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5306-00-298-3008

Externally Relieved Body Bolt - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A003b0