NSN 5306-00-298-4199

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-298-4199

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.625 inches
Fastener Length:
5.140 inches
Head Style:
Hexagon
Head Height:
0.203 inches
Width Between Flats:
0.562 inches
Shank Unthreaded Hole Diameter:
0.106 inches first hole
Thread Diameter:
0.375 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 127000 pounds per square inch
127000 pounds per square inch
127000 pounds per square inch Hardness Rating:
127000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c
 127000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center:
 127000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 4.969 inches first hole
 127000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 4.969 inches first hole Material:
 127000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 4.969 inches first hole Material: Steel comp 2330
 127000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 4.969 inches first hole Material: Steel comp 2330 Material Specification:
 127000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 4.969 inches first hole Material: Steel comp 2330 Material Specification: Sae assn standard single material response
 127000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 4.969 inches first hole Material: Steel comp 2330 Material Specification: Sae assn standard single material response Surface Treatment:
 127000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 4.969 inches first hole Material: Steel comp 2330 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium
 127000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 4.969 inches first hole Material: Steel comp 2330 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Thread Series Designator:
127000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 4.969 inches first hole Material: Steel comp 2330 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Thread Series Designator: Unf
 127000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 4.969 inches first hole Material: Steel comp 2330 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Thread Series Designator: Unf Shelf Life:
127000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 4.969 inches first hole Material: Steel comp 2330 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Thread Series Designator: Unf Shelf Life: N/a

No

NSN 5306-00-298-4199 Machine Bolt - Page 2 of 2

Fiig: A003b0

