NSN 5306-00-298-4464

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-298-4464 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.688 inches **Fastener Length:** Between 3.031 inches and 3.156 inches **Head Style:** Hexagon **Head Height:** 0.500 inches Width Between Flats: 0.875 inches **Shoulder Diameter:** 0.625 inches first shoulder **Shoulder Length:** 3.078 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.109 inches first hole **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Hardness Rating: 95.0 rockwell c and 99.0 rockwell c Minimum Yield Strength: 90000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 3.625 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel comp 1045 **Material Specification:** Sae assn standard single material response **Surface Treatment:** Cadmium **Thread Series Designator:**

Unf Shelf Life:

N/a

NSN 5306-00-298-4464 Shoulder Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

Demilitarization:

No

Fiig:

A003b0