NSN 5306-00-298-4872

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-298-4872 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.700 inches **Fastener Length:** 1.220 inches **Head Style:** Dee chamfer **Head Diameter:** Between 0.871 inches and 0.875 inches **Head Height:** 0.260 inches **Distance From Centerline To Flat:** 0.531 inches **Shank Unthreaded Hole Diameter:** 0.094 inches first hole **First Diameter From Head:** Between 0.494 inches and 0.500 inches **Second Diameter From Head:** Between 0.434 inches and 0.438 inches **Third Diameter From Head:** Between 0.491 inches and 0.500 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.120 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.420 inches and 0.460 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 0.480 inches and 0.560 inches **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 **Hardness Rating:** 32.0 rockwell c and 36.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: **Externally Relieved Body Diameter Quantity:**

1.080 inches first hole 3 Material: Steel

NSN 5306-00-298-4872

Externally Relieved Body Bolt - Page 2 of 2



| Surface Treatment: |
|---------------------------|
| Cadmium |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A003b0