

View Online at <https://aerobasegroup.com/nsn/5306-00-298-9204>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.260 inches and 1.300 inches

**Fastener Length:**

Between 7.410 inches and 7.450 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.395 inches and 0.415 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Extended Washer Diameter:**

Between 0.820 inches and 0.840 inches

**Extended Washer Thickness:**

Between 0.065 inches and 0.085 inches

**First Diameter From Head:**

Between 0.373 inches and 0.374 inches

**Second Diameter From Head:**

Between 0.315 inches and 0.320 inches

**Third Diameter From Head:**

Between 0.373 inches and 0.374 inches

**Fourth Diameter From Head:**

Between 0.315 inches and 0.320 inches

**Fifth Diameter From Head:**

Between 0.373 inches and 0.374 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.400 inches and 0.440 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 3.400 inches and 3.440 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 3.780 inches and 3.860 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

Between 5.690 inches and 5.810 inches

**Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:**

Between 6.070 inches and 6.230 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

210000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

5

**Material:**

Steel

**Material Specification:**

Ams 5629 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0