

View Online at <https://aerobasegroup.com/nsn/5306-00-300-2661>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.236 inches and 0.318 inches

Fastener Length:

Between 0.810 inches and 0.830 inches

Head Style:

Dished hexagon

Head Height:

Between 0.095 inches and 0.110 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Locking Feature:

Detent ring grip

Grip Diameter:

Between 0.1885 inches and 0.1894 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Thread Diameter:

0.190 inches

Grip Length:

Between 0.438 inches and 0.454 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

95000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 41.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.717 inches first hole and 0.747 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 4130 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0