NSN 5306-00-302-8652

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-302-8652 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.490 inches and 0.510 inches **Fastener Length:** Between 3.740 inches and 3.760 inches **Head Style:** Hexagon **Head Height:** Between 0.270 inches and 0.290 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Hole Diameter:** 0.062 inches First Diameter From Head: Between 0.309 inches and 0.312 inches **Second Diameter From Head:** Between 0.240 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.230 inches and 0.270 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 3.230 inches and 3.270 inches **Thread Diameter:** 0.312 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Hexagon flats **Externally Relieved Body Diameter Quantity:** 2 Material:

Steel comp 8740

Material Specification:

Ams 6322 assn standard single material response

NSN 5306-00-302-8652

Externally Relieved Body Bolt - Page 2 of 2



| Surface Treatment: |
|--|
| Cadmium |
| Surface Treatment Specification: |
| Ams 2400 assn standard single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A003b0