## NSN 5306-00-302-9084

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-302-9084 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.555 inches and 0.560 inches **Fastener Length:** 1.439 inches **Head Style:** Hexagon extended washer **Head Height:** 0.499 inches Width Between Flats: Between 0.428 inches and 0.440 inches **Extended Washer Diameter:** Between 0.620 inches and 0.621 inches **Extended Washer Thickness:** 0.340 inches **Shoulder Diameter:** 0.495 inches first shoulder and 0.505 inches first shoulder **Shoulder Length:** 0.819 inches first shoulder and 0.824 inches first shoulder **Hole Diameter:** 0.062 inches **Thread Diameter:** 0.375 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): **Hole Configuration Style:** Hexagon flats **Shoulder Shape:** Round first shoulder Material: Steel comp 4130 **Material Specification:** Mil-s-6758, cond d military specification single material response **Thread Series Designator:** Unf

## NSN 5306-00-302-9084

Shoulder Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-s-6758 spec.

Shelf Life: