

View Online at <https://aerobasegroup.com/nsn/5306-00-303-1359>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.750 inches and 0.810 inches

**Fastener Length:**

2.930 inches

**Head Diameter:**

Between 2.283 inches and 2.285 inches

**Head Height:**

0.580 inches

**Shank Unthreaded Hole Diameter:**

0.096 inches and 0.103 inches first hole

**First Diameter From Head:**

Between 0.282 inches and 0.292 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 2.120 inches and 2.180 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.790 inches first hole

**Externally Relieved Body Diameter Quantity:**

1

**Product Name:**

Navy special project

**Special Features:**

Countersunk hole in point and head; two holes in threaded area 0.063 com bination drill 60 degrees countersunk to 0.130-0.170 dia; head chamfer 0.100 in nom, indented 0.940-0.980 in.Dia top of head; sides of head relieved 0.250 in.Lg, extended portion of head 0.100 in.Lg.

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0