NSN 5306-00-308-3462 Internal Wrenching Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-00-308-3462 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.187 inches |
| Fastener Length: |
| Between 6.046 inches and 6.077 inches |
| Head Style: |
| Bevel-conical |
| Head Diameter: |
| Between 1.424 inches and 1.438 inches |
| Head Height: |
| 0.846 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.875 inches |
| Width Across Flats: |
| Between 0.751 inches and 0.755 inches |
| Thready Qty Per Inch (tpi): |
| 14 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Product Name: |
| Navy special project |
| Special Features: |
| Head flatted on two sides 0.990 in. Across flats |
| Material: |
| Stainless steel |
| Material Specification: |
| Qq-s-624, comp 3135 federal specification single material response or qq-s-624 comp 3140 federal specification single material response |
| or mil-s-5000 comp 4340 military specification single material response or mil-s-6049 comp 8740 military specification single material |
| response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5306-00-308-3462

Internal Wrenching Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.