

View Online at <https://aerobasegroup.com/nsn/5306-00-308-3603>

**Thread Direction:**

Right-hand

**Thread Length:**

0.792 inches

**Fastener Length:**

1.438 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

0.385 inches

**Head Height:**

0.047 inches

**Shank Unthreaded Hole Diameter:**

0.047 inches first hole

**First Diameter From Head:**

Between 0.308 inches and 0.310 inches

**Second Diameter From Head:**

Between 0.199 inches and 0.201 inches

**Third Diameter From Head:**

Between 0.308 inches and 0.310 inches

**Fourth Diameter From Head:**

Between 0.166 inches and 0.176 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.375 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.469 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

0.516 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

0.656 inches

**Thread Diameter:**

0.250 inches

**Nonstandard Thread Pitch Diameter:**

+0.2099/+0.2125 inches

**Thready Qty Per Inch (tpi):**

20

**Hardness Rating:**

26.0 rockwell c and 33.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.376 inches all holes

**Externally Relieved Body Diameter Quantity:**

4

**Material:**

Steel comp 416f

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Es-091, fscm 06848 mfr ref single treatment response

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0