

View Online at <https://aerobasegroup.com/nsn/5306-00-316-5557>

**Threads Per Inch:**

24 concentric hole

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.150 inches

**Fastener Length:**

4.500 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.312 inches and 0.327 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Shoulder Diameter:**

Between 0.6243 inches and 0.6248 inches

**Shoulder Length:**

2.870 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Concentric Hole Depth:**

0.810 inches

**Concentric Hole Diameter:**

0.375 inches

**Internal Thread Length:**

0.560 inches concentric hole

**Thread Diameter:**

0.375 inches

**Thread Series:**

Unjf concentric hole

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Thread Size:**

0.375 inches concentric hole

**Criticality Code Justification:**

Aavh

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.200 inches first hole

**Material:**

Steel comp e4340

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Lc+77-1061, cl 2, type 2, 36659 mfr ref single treatment response

**Style Designator:**

Concentric hole threaded

**Test Data Document:**

36659-alc+72-2014 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0