

View Online at <https://aerobasegroup.com/nsn/5306-00-316-5578>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.850 inches and 0.860 inches

Fastener Length:

5.790 inches

Shoulder Diameter:

Between 1.4990 inches and 1.4998 inches

Shoulder Length:

Between 4.680 inches and 4.690 inches

Shank Unthreaded Hole Diameter:

0.139 inches first hole and 0.145 inches first hole

Counterbore Diameter:

Between 0.9375 inches and 0.9390 inches

Counterbore Depth:

5.450 inches

Concentric Hole Diameter:

Between 0.564 inches and 0.566 inches

Thread Diameter:

1.250 inches

Thready Qty Per Inch (tpi):

16

Criticality Code Justification:

Aawy and aavh

Distance From Head Largest Bearing Surface To Shank Hole Center:

5.370 inches first hole and 5.380 inches first hole

Special Features:

Color white

Material:

Steel

Material Specification:

C-05-1190, fscm 36659 mfr ref single material response

Surface Treatment:

Paint

Surface Treatment Specification:

595 no. 17875 federal standard single treatment response

Style Designator:

Counterbore unthreaded

Test Data Document:

36659-lc+72-1076 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unj

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0