NSN 5306-00-316-9643

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-316-9643 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.525 inches **Fastener Length:** 4.500 inches **Head Style:** Hexagon **Head Height:** 0.250 inches Width Between Flats: 2.300 inches **Shoulder Diameter:** Between 0.9986 inches and 1.9995 inches **Shoulder Length:** Between 3.810 inches and 3.815 inches **Shank Unthreaded Hole Diameter:** 0.141 inches first hole and 0.166 inches first hole **Concentric Hole Diameter:** 1.250 inches **Thread Diameter:** 1.750 inches Thready Qty Per Inch (tpi): 16 **Special Features:** Undercut 0.090 in. Long with 0.020 in. Min, 0.030 in. Maximum undercut radius, located next to head Material: Steel **Material Specification:** Mil-s-5626 military specification single material response or mil-s-5000 military specification single material response or mil-s-6050 military specification single material response **Precious Material:** Silver **Surface Treatment:** Silver **Style Designator:** Concentric hole unthreaded

N/a

Un

Shelf Life:

Thread Series Designator:

NSN 5306-00-316-9643

Internally Relieved Body Bolt - Page 2 of 2



ı	In	iŧ	Of	Measure:
L	,,,	11	VI.	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.