NSN 5306-00-321-2294



Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-321-2294

Thread Class:
3a

Thread Direction:
Right-hand
Thread Length:
Between 0.589 inches and 0.639 inches

Fastener Length:
Between 1.224 inches and 1.254 inches

Head Style:
Double hexagon w/hole

Head Height:
Between 0.378 inches and 0.398 inches

Width Between Flats:

Between 0.429 inches and 0.449 inches

Detween 0.429 inches and 0.449 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

Between 0.081 inches and 0.101 inches

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 0.615 inches and 0.635 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Material:

Steel comp 8660h

Material Specification:

Aisi assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5306-00-321-2294

Shear Bolt - Page 2 of 2



Demi			

No

Fiig:

A003b0