

View Online at <https://aerobasegroup.com/nsn/5306-00-321-4622>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.355 inches and 0.365 inches

Fastener Length:

3.530 inches

Head Style:

Round w/wrench flats chamfered

Head Diameter:

1.000 inches

Head Height:

0.156 inches

Width Between Flats:

0.870 inches

Shoulder Diameter:

Between 0.623 inches and 0.624 inches

Shoulder Length:

Between 3.090 inches and 3.100 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Concentric Hole Diameter:

0.280 inches

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

20

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.375 inches first hole

Material:

Steel comp 4140

Material Specification:

Mil-s-5626 cond b military specification single material response

Surface Treatment:

Chromium

Surface Treatment Specification:

Ps13102 fscm 76301 mfr ref single treatment response

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.