NSN 5306-00-322-1607

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-322-1607

1a Thread Direction: Right-hand Thread Length: 0.320 inches Fastener Length: 0.462 inches Head Style: Double hexagon extended washer Head Height: 0.330 inches Width Between Flats: 0.309 inches Extended Washer Diameter: 0.438 inches Extended Washer Thickness: 0.045 inches Shank Unthreaded Hole Diameter: 0.500 inches first hole Thread Diameter: 0.250 inches Grip Length: 0.412 inches Factures Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 3.0.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Se	
Inread Direction:Right-handInread Length:0.320 inchesFastener Length:0.462 inchesHead Style:Double hexagon extended washerHead Height:0.330 inchesWith Between Flats:0.309 inchesExtended Washer Diameter:0.438 inchesExtended Washer Thickness:0.045 inchesShank Unthreaded Hole Diameter:0.050 inches first holeThread Diameter:0.250 inchesGrip Length:0.142 inchesFatures Provided:Finished headThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):136000 pounds per square inchHardness Rating:0.0.1000 pounds per square inchHardness Rating:0.1000 pounds per square inchHardness Rating:0.1000 pounds per square inchHardness Rating:0.1000 pounds per square inchHardness Rating:10.1000 pounds per square inchHardness Rating:10.1000 pounds per square inchHardness Rating:10.1000 pounds per square inch	Thread Class:
Right-hand Thread Length: 0.320 inches Fastener Length: 0.462 inches Head Style: Double hexagon extended washer Head Height: 0.330 inches Width Between Flats: 0.309 inches Extended Washer Diameter: 0.438 inches Extended Washer Thickness: 0.045 inches Shank Unthreaded Hole Diameter: 0.045 inches Grip Length: 0.425 inches Fatended Washer Thickness: 0.045 inches Shank Unthreaded Hole Diameter: 0.045 inches Grip Length: 0.425 inches Fatures Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: <	
Tread Length: 0.320 inches Fastener Length: 0.462 inches Head Style: Double hexagon extended washer Head Height: 0.330 inches Width Between Flats: 0.309 inches Extended Washer Diameter: 0.438 inches Extended Washer Thickness: 0.4438 inches Shank Unthreaded Hole Diameter: 0.045 inches Staned Washer Thickness: 0.405 inches Shank Unthreaded Hole Diameter: 0.455 inches Stanke Unthreaded Hole Diameter: 0.450 inches Thread Diameter: 0.450 inches Fished head Thread Provided: Finshed head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 0.302 inches first hole Material: 136000 pounds per square inch Hardness Rating: 0.302 inches first hole Material: 136100 pounds p	
0.320 inchesFastener Length:0.462 inchesHead Style:Double hexagon extended washerHead Height:0.330 inchesWidth Between Flats:0.309 inchesExtended Washer Diameter:0.438 inchesExtended Washer Thickness:0.451 inchesStank Unthreaded Hole Diameter:0.455 inchesStank Unthreaded Hole Diameter:0.450 inchesGrip Length:0.450 inchesFatended Washer Thickness:0.450 inchesFatended Hole Diameter:0.450 inchesGrip Length:0.450 inchesFatures Provided:Finished headThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):136000 pounds per square inchHardness Rating:0.362 inches first holeDistance From Head Largest Bearing Surface To Shank Hole Center:0.362 inches first holeMaterial:Stankes steelMaterial:Stankes steelMaterial Specification:Ams 5616 assen standard single material responseThread Series Designator:UnfShelf Life:	-
Fastener Length:0.462 inchesHead Style:Double hexagon extended washerHead Height:0.330 inchesWidth Between Flats:0.309 inchesExtended Washer Diameter:0.438 inchesExtended Washer Thickness:0.045 inchesShank Unthreaded Hole Diameter:0.050 inches first holeThread Diameter:0.250 inchesGrip Length:0.142 inchesFatures Provided:Finished headThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):136000 pounds per square inchHardness Rating:0.032 inches first holeDistance From Head Largest Bearing Surface To Shank Hole Center:0.362 inches strelMaterial:Stankes SteelMaterial:Stankes SteelMaterial:Chread Specification:Ains 5616 assn standard single material responseCircel Series Designator:UrfShell Life:	
0.462 inchesHead Style:Double hexagon extended washerHead Height:0.330 inchesWidth Between Flats:0.309 inchesExtended Washer Diameter:0.438 inchesExtended Washer Thickness:0.045 inchesShank Unthreaded Hole Diameter:0.050 inches first holeThread Diameter:0.250 inchesGrip Length:0.142 inchesFatures Provided:Finished headThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):136000 pounds per square inchHardness Rating:30.0 rockwell c and 38.0 rockwell cDistance From Head Largest Bearing Surface To Shank Hole Center:0.362 inches dirst holeHartnal:Stainless steelMaterial:Stainless steelMaterial Specification:Arns 6316 assn standard single material responseThread Series Designator:UrfShell Life:	
Head Style: Double hexagon extended washer Head Height: 0.330 inches Width Between Flats: 0.309 inches Extended Washer Diameter: 0.438 inches Extended Washer Thickness: 0.045 inches Shank Unthreaded Hole Diameter: 0.050 inches first hole Thread Diameter: 0.250 inches Grip Length: 0.142 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Arns 5616 assn standard single material response Thread Series Designator: Unf	-
Double hexagon extended washerHead Height:0.330 inchesWidth Between Flats:0.309 inchesExtended Washer Diameter:0.438 inchesExtended Washer Thickness:0.045 inchesShank Unthreaded Hole Diameter:0.050 inches first holeThread Diameter:0.250 inchesGrip Length:0.142 inchesFatures Provided:Finished headThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):136000 pounds per square inchHardness Rating:0.362 inches first holeDistance From Head Largest Bearing Surface To Shank Hole Center:0.362 inches first holeHartnel:Stainless steelMaterial:Stainless steelMaterial Specification:Ams 5016 assn standard single material responseThread Series Designator:UnfShelf Life:	0.462 inches
Head Heigh:0.330 inchesWidth Between Flats:0.309 inchesExtended Washer Diameter:0.438 inchesExtended Washer Thickness:0.045 inchesShank Unthreaded Hole Diameter:0.050 inches first holeThread Diameter:0.250 inchesGrip Length:0.142 inchesFatures Provided:Finished headThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):136000 pounds per square inchHardness Rating:0.030 rockwell c and 38.0 rockwell c0.362 inches first holeMaterial:Stainless steelMaterial Specification:Ams 5616 assn standard single material responseThread Series Designator:UriShelf Life:	Head Style:
0.330 inches Width Between Flats: 0.309 inches Extended Washer Diameter: 0.438 inches Extended Washer Thickness: 0.045 inches Shank Unthreaded Hole Diameter: 0.050 inches first hole Thread Diameter: 0.250 inches Grip Length: 0.142 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 0.302 inckes first hole Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Arms 5016 assn standard single material response Thread Series Designator: Unf Shelf Life:	Double hexagon extended washer
With Between Flats: 0.309 inches Extended Washer Diameter: 0.438 inches Extended Washer Thickness: 0.045 inches Shank Unthreaded Hole Diameter: 0.050 inches first hole Thread Diameter: 0.250 inches Grip Length: 0.142 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Anns 5616 assn standard single material response Thread Series Designator: Unf	Head Height:
0.309 inches Extended Washer Diameter: 0.438 inches Extended Washer Thickness: 0.045 inches Extended Hole Diameter: 0.050 inches first hole Thread Diameter: 0.250 inches Grip Length: 0.142 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 0.060 pounds per square inch Hardness Rating: 0.362 inches first hole Material: Stainless steel MaterialSpecification: Ams 5616 assn standard single material response Infe ad Series Designator: Unf Shelf Life:	0.330 inches
Extended Washer Diameter: 0.438 inches Extended Washer Thickness: 0.045 inches Shank Unthreaded Hole Diameter: 0.050 inches first hole Thread Diameter: 0.250 inches Grip Length: 0.250 inches Grip Length: 0.142 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Arms 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	Width Between Flats:
0.438 inches Extended Washer Thickness: 0.045 inches Shank Unthreaded Hole Diameter: 0.050 inches first hole Thread Diameter: 0.250 inches Grip Length: 0.142 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material: Chard Specification: Ams 5616 assn standard single material response Infreed Series Designator: Unf Shelf Life:	0.309 inches
Extended Washer Thickness: 0.045 inches Shank Unthreaded Hole Diameter: 0.050 inches first hole Thread Diameter: 0.250 inches Grip Length: 0.142 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	Extended Washer Diameter:
0.045 inches Shank Unthreaded Hole Diameter: 0.050 inches first hole Thread Diameter: 0.250 inches Grip Length: 0.142 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	0.438 inches
Shank Unthreaded Hole Diameter: 0.050 inches first hole Thread Diameter: 0.250 inches Grip Length: 0.142 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	Extended Washer Thickness:
0.050 inches first hole Thread Diameter: 0.250 inches Grip Length: 0.142 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	0.045 inches
Thread Diameter:0.250 inchesGrip Length:0.142 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):136000 pounds per square inchHardness Rating:30.0 rockwell c and 38.0 rockwell cDistance From Head Largest Bearing Surface To Shank Hole Center:0.362 inches first holeMaterial:Stainless steelMaterial Specification:Ams 5616 assn standard single material responseThread Series Designator:UnfShelf Life:	Shank Unthreaded Hole Diameter:
0.250 inches Grip Length: 0.142 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	0.050 inches first hole
Grip Length: 0.142 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	Thread Diameter:
0.142 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	0.250 inches
Features Provided:Finished headThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):136000 pounds per square inchHardness Rating:30.0 rockwell c and 38.0 rockwell cDistance From Head Largest Bearing Surface To Shank Hole Center:0.362 inches first holeMaterial:Stainless steelMaterial Specification:Ams 5616 assn standard single material responseThread Series Designator:UnfShelf Life:	Grip Length:
Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	0.142 inches
Thready Qty Per Inch (tpi):28Min. Tensile Strength (psi):136000 pounds per square inchHardness Rating:30.0 rockwell c and 38.0 rockwell cDistance From Head Largest Bearing Surface To Shank Hole Center:0.362 inches first holeMaterial:Stainless steelMaterial Specification:Ams 5616 assn standard single material responseThread Series Designator:UnfShelf Life:	Features Provided:
28 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	Finished head
 Min. Tensile Strength (psi): 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life: 	Thready Qty Per Inch (tpi):
 136000 pounds per square inch Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life: 	28
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	Min. Tensile Strength (psi):
30.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	136000 pounds per square inch
Distance From Head Largest Bearing Surface To Shank Hole Center: 0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	Hardness Rating:
0.362 inches first hole Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	30.0 rockwell c and 38.0 rockwell c
Material: Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	Distance From Head Largest Bearing Surface To Shank Hole Center:
Stainless steel Material Specification: Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	0.362 inches first hole
Material Specification:Ams 5616 assn standard single material responseThread Series Designator:UnfShelf Life:	Material:
Ams 5616 assn standard single material response Thread Series Designator: Unf Shelf Life:	Stainless steel
Thread Series Designator: Unf Shelf Life:	Material Specification:
Unf Shelf Life:	Ams 5616 assn standard single material response
Shelf Life:	Thread Series Designator:
	Unf
N/a	Shelf Life:
TV/d	N/a

NSN 5306-00-322-1607

Machine Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

