

View Online at <https://aerobasegroup.com/nsn/5306-00-322-1609>

**Thread Class:**

1a

**Thread Direction:**

Right-hand

**Thread Length:**

0.355 inches

**Fastener Length:**

Between 0.490 inches and 0.510 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.320 inches and 0.340 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

**Shank Unthreaded Hole Diameter:**

0.047 inches first hole and 0.053 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.350 inches and 0.360 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

130000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.395 inches first hole and 0.405 inches first hole

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5735 assn standard single material response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0