

View Online at <https://aerobasegroup.com/nsn/5306-00-326-4775>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.428 inches and 0.478 inches

**Fastener Length:**

Between 1.938 inches and 1.968 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.219 inches and 0.234 inches

**Width Between Flats:**

Between 0.679 inches and 0.690 inches

**Grip Diameter:**

Between 0.4365 inches and 0.4370 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 1.490 inches and 1.510 inches

**Thready Qty Per Inch (tpi):**

20

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.803 inches first hole and 1.853 inches first hole

**Surface Finish:**

63.0 microinches grip

**Material:**

Titanium alloy

**Material Specification:**

Nas 621 assn standard single material response or ams 4928 assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas657 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0