

View Online at <https://aerobasegroup.com/nsn/5306-00-326-4854>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.428 inches and 0.478 inches

Fastener Length:

Between 2.750 inches and 2.780 inches

Head Style:

Hexagon

Head Height:

Between 0.219 inches and 0.234 inches

Width Between Flats:

Between 0.679 inches and 0.690 inches

Grip Diameter:

Between 0.4365 inches and 0.4370 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.437 inches

Grip Length:

Between 2.302 inches and 2.322 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.615 inches first hole and 2.665 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas657 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0