## NSN 5306-00-326-4860

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-326-4860 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.428 inches and 0.478 inches **Fastener Length:** Between 4.563 inches and 4.593 inches **Head Style:** Hexagon **Head Height:** Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Grip Diameter:** Between 0.4990 inches and 0.4995 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.116 inches first hole **Thread Diameter:** 0.500 inches **Grip Length:** Between 4.115 inches and 4.135 inches Thready Qty Per Inch (tpi): 20 Distance From Head Largest Bearing Surface To Shank Hole Center: 4.428 inches first hole and 4.478 inches first hole **Surface Finish:** 63.0 microinches grip Material: Titanium alloy **Material Specification:** Nas 621 assn standard single material response or ams 4928 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas658 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5306-00-326-4860

Close Tolerance Bolt - Page 2 of 2



Fiig:

A003b0