

View Online at <https://aerobasegroup.com/nsn/5306-00-329-1614>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.479 inches

Fastener Length:

4.164 inches

Head Style:

Round w/wrench flats chamfered

Head Diameter:

1.375 inches

Head Height:

0.156 inches

Width Between Flats:

1.125 inches

Shank Unthreaded Hole Diameter:

0.140 inches first hole and 0.146 inches first hole

Concentric Hole Diameter:

0.650 inches

Thread Diameter:

1.000 inches

Thready Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.985 inches first hole

Material:

Steel

Material Specification:

Mil-s-5000 cond c military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ps13145 type 2 cl 2 fscm 76301 mfr ref single treatment response

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.