

View Online at <https://aerobasegroup.com/nsn/5306-00-329-1614>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.479 inches

**Fastener Length:**

4.164 inches

**Head Style:**

Round w/wrench flats chamfered

**Head Diameter:**

1.375 inches

**Head Height:**

0.156 inches

**Width Between Flats:**

1.125 inches

**Shank Unthreaded Hole Diameter:**

0.140 inches first hole and 0.146 inches first hole

**Concentric Hole Diameter:**

0.650 inches

**Thread Diameter:**

1.000 inches

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.985 inches first hole

**Material:**

Steel

**Material Specification:**

Mil-s-5000 cond c military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ps13145 type 2 cl 2 fscm 76301 mfr ref single treatment response

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.