Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-331-2239

| Thread Class: | |
|---------------------|--|
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.375 inches | |
| Fastener Length: | |
| 1.500 inches | |
| Head Style: | |
| Hexagon | |
| Head Height: | |
| 0.375 inches | |
| Width Between Fla | is: |
| 1.000 inches | |
| First Diameter From | n Head: |
| 0.650 inches | |
| Distance From Lar | gest Bearing Surface Of Head To End Of First Diameter: |
| 1.125 inches | |
| Thread Diameter: | |
| 0.750 inches | |
| Thready Qty Per In | ch (tpi): |
| 16 | |
| Hardness Rating: | |
| 25.0 rockwell c | |
| Externally Relieved | Body Diameter Quantity: |
| 1 | |
| Material: | |
| Steel comp 4145 | |
| Surface Treatment | |
| Zinc and phosphate | |
| Thread Series Des | gnator: |
| Unf | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A003b0 | |