## NSN 5306-00-332-4746

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-332-4746

Three d Olever
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.475 inches and 0.525 inches
Fastener Length:
Between 0.875 inches and 0.890 inches
Head Style:
Double hexagon w/hole
Head Height:
0.254 inches
Width Between Flats:
Between 0.304 inches and 0.313 inches
Extended Washer Diameter:
Between 0.465 inches and 0.475 inches
Extended Washer Thickness:
0.042 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.365 inches and 0.385 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Material:
Steel
Material Specification:
Sps-m-107, fscm 50394 mfr ref single material response
Surface Treatment:
Nickel and cadmium
Surface Treatment Specification:
Ams 2416 assn standard all treatment responses
Thread Series Designator:
Unjf

**Specification Data:** 

50394-ewbt-9 manufacturers standard

## NSN 5306-00-332-4746

Shear Bolt - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0