NSN 5306-00-332-4746

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-332-4746

Three d Olever					
Thread Class:					
3a					
Thread Direction:					
Right-hand					
Thread Length:					
Between 0.475 inches and 0.525 inches					
Fastener Length:					
Between 0.875 inches and 0.890 inches					
Head Style:					
Double hexagon w/hole					
Head Height:					
0.254 inches					
Width Between Flats:					
Between 0.304 inches and 0.313 inches					
Extended Washer Diameter:					
Between 0.465 inches and 0.475 inches					
Extended Washer Thickness:					
0.042 inches					
Grip Diameter:					
Between 0.2485 inches and 0.2495 inches					
Thread Diameter:					
0.250 inches					
Grip Length:					
Between 0.365 inches and 0.385 inches					
Thready Qty Per Inch (tpi):					
28					
Min. Tensile Strength (psi):					
220000 pounds per square inch					
Hardness Rating:					
46.0 rockwell c and 50.0 rockwell c					
Material:					
Steel					
Material Specification:					
Sps-m-107, fscm 50394 mfr ref single material response					
Surface Treatment:					
Nickel and cadmium					
Surface Treatment Specification:					
Ams 2416 assn standard all treatment responses					
Thread Series Designator:					
Unjf					

Specification Data:

50394-ewbt-9 manufacturers standard

NSN 5306-00-332-4746

Shear Bolt - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0