## NSN 5306-00-335-2223

Externally Relieved Body Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-00-335-2223            |
|--|
| Thread Class:  |
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.410 inches   |
| Fastener Length:   |
| 1.000 inches   |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| 0.312 inches   |
| Head Height:   |
| 0.190 inches   |
| First Diameter From Head:  |
| 0.190 inches   |
| Second Diameter From Head:   |
| 0.140 inches   |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter:  |
| 0.035 inches   |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| 0.625 inches   |
| Thread Diameter:   |
| 0.190 inches   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Externally Relieved Body Diameter Quantity:                              |
| 1  |
| Material:  |
| Stainless steel  |
| Surface Treatment:   |
| Oxide  |
| Surface Treatment Specification:   |
| Mil-c-13924 military specification single treatment response             |
| Thread Series Designator:  |
| Unf  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |

No

## NSN 5306-00-335-2223

Externally Relieved Body Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.