NSN 5306-00-335-4376

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-335-4376 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.181 inches and 0.186 inches **Fastener Length:** Between 0.295 inches and 0.320 inches **Head Style:** Hexagon extended washer **Head Height:** Between 0.155 inches and 0.188 inches Width Between Flats: Between 0.365 inches and 0.382 inches **Extended Washer Diameter:** 0.500 inches **Extended Washer Thickness:** Between 0.038 inches and 0.048 inches **First Diameter From Head:** Between 0.180 inches and 0.185 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.094 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity: Special Features:** 0.180 in. Min. 0.185 in. Maximum diameter by 0.020 in. Min, 0.040 in. Maximum Ig point at thd end Material: Steel comp 1008 **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** +44e, fscm 19207 military specification 1st treatment response and +10c, fscm 19207 military specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5306-00-335-4376

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

spec.